

LuxCreo iLuxWash Dental

iLuxWash Dental enhances the ultrasonic cleaning process by adding a magnetic-driven impeller stirring function. This rapidly agitates the cleaning solution during ultrasonic cleaning while also featuring a heating function, making it more effective in removing residual resin from printed parts.

Driven by a focus on improving user experience, the fully-automatic intelligent operating system enables unattended and automatic operations. This helps prevent distortion issues that may arise from over-soaking printed parts, making iLuxWash Dental the best choice in the dental and medical fields.

iLuxWash Dental



SYSTEM SPECIFICATIONS	
Washing Volume(XYZ)	160 x 160 x 148 mm(6.3 x 6.3 x 5.8 in)
Exterior Dimension Uncrated	200 x 488 x 418 mm(7.9 x 19.2 x 16.5 in)
Exterior Dimension Crated	615 x 335 x 525 mm(24.2 x 13.2 x 20.7 in)
Uncrated Weight	17.5 kg(38.6 lbs)
Crated Weight	21.5 kg(47.4 lbs)
Heating Temperature	≤60°C
LCD Screen	4.3" HMI, Touch Screen
Warranty	12 months manufacturer's warranty included
	Extended warranty options available
SUGGESTED OPERATING ENVIRONMENT	
Temperature	22-32 °C (72-90 °F)
Humidity (RH)	<80%
Power Requirement	110/220VAC, 60/50 Hz, 150 W
SOFTWARE AND NETWORK	
Connectivity	USB

iLuxWash Dental SPECIFICATIONS www.LuxCreo.com